09 — Tebex Bridge

Workspace Tebex setup, automatic activation and webhook behavior.

- Configuring Tebex
- Product Tebex Setup

Configuring Tebex

Configuring Tebex

Tebex can be configured per developer workspace.

Users with product or license management permissions can access the Tebex Bridge configuration.

Workspace settings

The integration supports:

- Enabled/disabled state
- Tebex Headless/public token
- Webhook secret
- Store URL
- Success URL
- Cancel URL

Nord Forge exposes the workspace's webhook URL for use in Tebex.

Environment fallback

Platform-level fallback values can be provided with:

```
TEBEX_HEADLESS_TOKEN=
TEBEX_PUBLIC_TOKEN=
TEBEX_WEBHOOK_SECRET=
```

Per-workspace configuration should be preferred when multiple developer stores use the same Forge platform.

Product Tebex Setup

Product Tebex Setup

To sell a product through Tebex:

1. Open the product editor.
2. Set **Payment** to `Tebex`.
3. Enter the correct **Tebex Package ID**.
4. Configure the product license type and duration.
5. Make sure checkout is enabled.
6. Configure the workspace Tebex Bridge.
7. Publish a release with a file.
8. Publish the product.
9. Test checkout and webhook activation.

After a valid payment webhook, Nord Forge can automatically associate the product with the customer's Forge Key.